

Wide Format Laminate

RSH-380SL



- Same features as RSH-380
- Large film roll capacity (up to 200mm / 7.9" diameter)
- **De-Curling device for the high quality of single laminating**
- **Double & Single (OPP film) Laminating function**
- **Low price**

RSH-380



- High quality thermal encapsulation
- Fast, up to 5m/min / 16.5ft/min
- Accepts thick substrates (up to 6mm/0.24")
- STAND-BY function: Power saving & Auto shut off
- Large film roll capacity (up to 280mm / 11" diameter)

MODEL		RSH-380SL	RSH-380
MAKER		RS	RS
Power supply		AC100-120V, 220~240V 50/60Hz	AC100, 200, 220~240V 50/60Hz 120V 60Hz
Power consumption		1200W	1500W
Display method		LED	LED
Max laminating width		380mm / 15"	380mm / 15"
Film thickness		25~250 mic (1~10mil) / Opp film 32mic	25 ~ 250mic / 1~10mil
Film diameter		200mm / 7.9"	280 mm / 11"
Single laminating		Yes	No
Mounting thickness		6mm / 0.24"	6mm / 0.24"
Paper thickness	Single	200~250g	Not Application
	Double	80~250g	80~250g
Max laminating speed		5 m/min / 16.4 ft/min	5 m/min / 16.4 ft/min
Speed control		9 settings	9 settings
Drive method		DC motor	DC geared
Ready time		8 min	8 min
Laminating method		Thermal	Thermal
Max Temperature		150°C / 302°F	150°C / 302°F
Hot lamination	Single	Yes	No
	Double	Yes	Yes
Cross Cutter		Yes	Yes
De-Curling device		Yes	No
Film core size		Auto grip (2.25", 3"), Core 1"	1", 2.25", 3"
Unit dimensions (w x d x h)		550 X 640 X 450 mm 21.5" x 25" x 17.7"	550 x 690 x 605 (mm) 21.5" x 27" x 24"
Unit weight		40kg / 88lbs	45kg / 99lbs